

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : B65D 77/06, 19/12		A1	(11) International Publication Number: WO 95/18754
			(43) International Publication Date: 13 July 1995 (13.07.95)
(21) International Application Number: PCT/NL95/00010		(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, MX, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SI, SK, TJ, TT, UA, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ).	
(22) International Filing Date: 5 January 1995 (05.01.95)			
(30) Priority Data: 9400029 7 January 1994 (07.01.94) NL			
(71) Applicant (for all designated States except US): KONINKLIJKE EMBALLAGE INDUSTRIE VAN LEER B.V. [NL/NL]; Amsterdamseweg 206, P.O. Box 25, NL-1180 AA Amstelveen (NL).		Published With international search report.	
(72) Inventors; and			
(75) Inventors/Applicants (for US only): VAN GIEZEN, Maurice, Gerardus, Maria [NL/NL]; Rijksweg 275R, NL-2024 DH Haarlem (NL). FEIJH, Harald [NL/NL]; Johan de Meesterstraat 32, NL-3532 EK Utrecht (NL).			
(74) Agent: DE BRUIJN, Leendert, C.; Nederlandsch Octrooibureau, Scheveningseweg 82, P.O. Box 29720, NL-2502 LS The Hague (NL).			

(54) Title: COLLAPSIBLE CONTAINER FOR FLUID PRODUCTS

(57) Abstract

A container device for bulk goods or liquid comprises a folding frame (1) and a container (2) accommodated in the frame, which frame comprises a base section (3) as well as at least two folding side sections (4, 5) provided on opposite sides of the base section, which side sections are movable between a horizontal position and an upright position. The frame has a top section (13) which is supported some distance above the base section and foldably interacts with one of the sides.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

COLLAPSIBLE CONTAINER FOR FLUID PRODUCTS

The invention relates to a container device for bulk goods or liquid, comprising a frame as well as a container accommodated in the frame. A  
5 container device of this type is known. The frame provides the actual container with rigidity as well as protection against external stresses such as arise during storage and transport. Moreover, it contributes to the dimensional stability of the container, including when the latter is completely filled. The container itself is suitable for bulk goods and  
10 liquids.

In connection with environmental requirements, packaging must be suitable for re-use. In practice this means that the packaging has to be returned separately, which, especially in the case of bulk packaging, is associated with drawbacks in view of the transport volume required for this.  
15 The known container device has the drawback that, despite the fact that the container itself can be made of flexible material, the empty container device, as a consequence of the rigid frame, still has the same volume as the full device.

The aim of the invention is, therefore, to overcome this disadvantage.  
20 This is achieved in that the frame can be folded up. In particular, the frame can comprise a base section as well as at least two foldable side sections provided on opposite sides of the base section, which side sections are movable between a horizontal position and an upright position.

Moreover, the frame can have a top section which is supported some  
25 distance above the base section and foldably interacts with one of the sides. With this arrangement, the sides and the top section can be folded about hinges, the centre lines of which are parallel to one another.

The container device can be folded up compactly if the hinges of the side connected to the top section are fitted some distance above the base  
30 section, in such a way that the top section folded against said side fits between the base section and said side folded on said base section. Furthermore, the hinges of the other side can be fitted a greater distance away from the base section, in such a way that said side can be folded onto the side carrying the top section. Nevertheless, the hinges can also be  
35 positioned such that the side with the top section can be folded on top of the other side.

Base section and sides are preferably constructed of tubular material, the base section being a tube which forms a one-piece unit essentially in

the form of a rectangle, two opposite sides of which are bent down close to the corners of the rectangle in such a way that the other two opposite sides are outside the plane described by the first two opposite sides. Those sides of the base section which are bent down provide an opening with respect to  
5 the floor or surface on which the base section rests. The container device can be lifted at this point by inserting the forks of a fork-lift truck in the opening.

The container device is particularly suitable for stacking in the filled state. To this end, the bottom of the base section and the tops of  
10 the sides have support points by means of which the device is stackable. The frame offers the requisite support for various container devices stacked on top of it.

However, stackability is also ensured in the folded state if the sides are hingably mounted in corner pieces which protrude above the sides and top  
15 section folded onto the base section.

According to a first possibility, the container is a sack made of flexible material, which preferably is fixed at its top edges to the top section. In order to obtain a shape which as far as possible approaches a block shape with a flexible sack of this type even when the latter is  
20 filled, the side walls of the sack are each fixed to the top section in such a way that the middle section of each wall has a lesser height than the sections located close to the corners of the sack.

The consequence of this shape is that the middle section of each side wall of the sack is subjected to higher tensile forces than the sections  
25 located closer to the corners of the sack. In this way, a corrective effect is obtained precisely in said middle section, which, after all, has the greatest tendency to bulge, as a result of which corrective effect the block shape can approximately be retained.

In this context, the side walls of the sack are each cut along a concave line at their top edge. If this top edge is now attached to the  
30 frame in a straight line, the shortening of the side walls in their middle section is obtained immediately.

A further improvement in this respect can be obtained if the base section is provided with a solid base and the bottom of the sack partially  
35 rests on the solid base.

The invention will be explained in more detail below with reference to an illustrative embodiment shown in the figures.

Fig. 1 shows a perspective view of the container device according to

the invention in the folded position.

Fig. 2 shows a perspective view of the container device in the partly unfolded position.

Fig. 3 shows a perspective view of the container device in the  
5 completely unfolded position, whilst it is still empty.

Fig. 4 shows a perspective view of the filled container device.

Fig. 5 shows a side view of two folded containers which are stackable on top of one another.

Fig. 6 shows a perspective view of two completely unfolded containers  
10 which are stacked on top of one another.

Fig. 7 shows an outline of the walls of the flexible sack.

Fig. 8 shows a section through the seam of the sack.

The container device shown in Fig. 1 comprises a frame, which is indicated in its entirety by 1, and a flexible sack, indicated by 2. The  
15 frame 1 has a base section 3 to which the two sides 4 and 5 are hingably connected by hinges 6 and 7 respectively.

In the embodiment shown the base section 3 is composed of a tube of circular cross-section which forms a rectangle and the sides 8 of which are bent downwards with respect to the other sides 9. Said sides 9 are therefore  
20 some distance away from the floor or surface on which the frame 1 is placed, such that the fork of a fork-lift truck can be introduced beneath the sides 9.

Furthermore, a base 10 is fitted between the sides 9, whilst support points are arranged close to the corners of the base section, which support  
25 points comprise L-shaped corner pieces 11 to which tube sections 12 are welded. Said corner pieces 11 also carry the hinges 6 and 7 for the sides 4 and 5 respectively.

As can be seen more clearly in Fig. 2, a top section 13 is hingably attached via spacers 14 to the side 4. The sack 2 is fixed, in a manner  
30 which will be described below, to said top section 13, which likewise comprises a one-piece tube, which in the example shown is of circular cross-section. Furthermore, the cover flap 26 for the sack 2 is fitted to the top section 13. A separate piece of material, which does not form part of the sack 2, can also be used for the flap 26.

35 The top section 13 is provided with flanges 15 on its side opposite the spacers 14, which flanges can be fixed, for example by means of associated clamps 16, which are accommodated in brackets 17, to the side 5 of the container device.

In the position shown in Fig. 3, the container device is completely folded open, the top section 13 being fixed to the side 5 by means of the said screw/nut connectors 16. The cover flap 26 is partly folded back. A band is fitted in the periphery of the cover flap 26, in such a way that the  
5 cover flap 26 can be fitted over the periphery of the top section 13, as a result of which the flexible sack 2 is closed off. Furthermore, the flexible sack 2 can be provided with an emptying opening 18.

In the position shown in Fig. 4, the container device according to the invention is completely filled. In this position, the walls of the container  
10 bulge slightly outwards, but only to a limited extent because of the connection, which will be described below, of the flexible sack 2 to the top section 13. In the position shown in Fig. 4, the cover flap 26 has been pulled down over the periphery of the top section 13 by means of its band. The emptying opening is also provided with a closure 25.

15 It can also be seen that the sides 4 and 5 are provided at their tops with support pieces 19 of L-shaped cross-section, on which another unfolded container device can be supported via its corner pieces 11, as will be explained in more detail.

The folded-up container devices shown in Fig. 5 can be stacked directly  
20 on top of one another by means of their corner pieces 11. In a stack, the tube sections 12, which protrude a little below the associated corner piece 11 and have a conical end 20 on that underside, fit inside the underlying corner piece 11, as a result of which stable stacking is ensured.

In the position shown in Fig. 6, two unfolded containers are stacked  
25 on one another. In this arrangement, the corner pieces 11 of the upper container rest on the support pieces 19 of an underlying container, the conical ends 20 of the upper container device fitting inside the support pieces 19. With this arrangement as well, stable stacking is ensured. Moreover, the conical shape of the ends 20 makes stacking easier.

30 Fig. 7 shows an outline of the side walls of the flexible sack 2. Each of said side walls 21 has a top edge 22 cut along a concave line. An associated strip of material is also shown at each top edge, which strip of material consists of two folded flaps 28 and 25, as shown in the cross-section in Figure 8. In this cross-section it can also be seen that flaps  
35 28 and 25 are each welded to the relevant side wall 21. With this arrangement, the middle of said side wall must be pulled upwards, in such a way that the concave lines 22 of the sack, and the strips 26, which are of opposite curvature, are pulled straight.

In this way a seam 27 is formed, in which a flat metal strip is inserted and which is fixed to a tube section of the top section.

Each top edge 22 is pulled a little upwards at the centre, as a result of which the folds 23 are formed, as shown in Fig. 3. As a consequence, the middle section of each side wall 21 is, as it were, pulled a little upwards. The consequence of this is that bulging of the flexible sack when the latter is filled is appreciably less than would be the case if the top edges 22 had been produced along a straight line. It is precisely in the middle of the side walls 21, where the tendency to bulging is greatest when the sack is filled, that the shape of the top edge provides for a relatively high tensile force, which produces a corrective effect against bulging.



Claims

1. Container device for bulk goods or liquid, comprising a folding frame as well as a container accommodated in the frame, which frame  
5 comprises a base section as well as at least two foldable side sections provided on opposite sides of the base section, which side sections are movable between a horizontal position and an upright position, characterised in that the frame has a top section which is supported some distance above the base section and foldably interacts with one of the sides.
- 10 2. Device according to Claim 1, wherein the sides and the top section can be folded about hinges, the centre lines of which are parallel to one another.
- 15 3. Device according to Claim 2, wherein the hinges of the side connected to the top section are fitted some distance above the base section, in such a way that the top section folded against said side fits between the base section and said side folded on said base section.
- 20 4. Device according to Claim 3, wherein the hinges of the other side are fitted a greater distance away from the base section, in such a way that said side can be folded onto the side carrying the top section.
- 25 5. Device according to one of Claims 1 - 4, wherein base section and sides are constructed of tubular material.
- 30 6. Device according to Claim 5, wherein the base section is a tube which forms a one-piece unit essentially in the form of a rectangle, two opposite sides of which are bent down close to the corners of the rectangle in such a way that the other two opposite sides are outside the plane described by the first two opposite sides.
- 35 7. Device according to one of Claims 1 - 6, wherein the bottom of the base section and the tops of the sides have support points by means of which the device is stackable.
8. Device according to Claim 7, wherein the sides are hingably mounted in corner pieces which protrude above the sides and top section folded onto




the base section, in such a way that the device is stackable when it is folded up.

9. Device according to one of the preceding claims, wherein the  
5 container is a sack made of flexible material.

10. Device according to Claim 9, wherein the sack is fixed to the top section at its top edges.

10 11. Device according to Claim 10, wherein the side walls of the sack are each cut along a concave line at their top edge and are each fixed to the top section in such a way that the middle section of each wall has a lesser height than the sections located close to the corners of the sack.

15 12. Device according to one of Claims 9 - 11, wherein the base section is provided with a solid base and the bottom of the sack at least partially rests on the solid base.



2/6

fig - 2






fig-3




4/6

fig - 4



5/6

fig-5







# INTERNATIONAL SEARCH REPORT

In ☐ National Application No  
PCT/NL 95/00010

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 B65D77/06 B65D19/12

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP,A,0 573 230 (FARELL) 8 December 1993 see column 6, line 45 - column 7, line 21; figures 1-4	1
A	DE,A,22 46 812 (CORDES) 28 March 1974 see claim 1; figures	1
A	DE,A,24 42 322 (OHRTMANN) 18 March 1976 see page 2, line 30 - page 3, line 14; figures 1,2	1

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*&\* document member of the same patent family

Date of the actual completion of the international search

4 April 1995

Date of mailing of the international search report

19. 04. 95

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+ 31-70) 340-3016

Authorized officer

Newell, P

# INTERNATIONAL SEARCH REPORT

Information on patent family members

Int. Application No

PCT/NL 95/00010

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-0573230	08-12-93	GB-A, B 2267481	08-12-93
DE-A-2246812	28-03-74	NONE	
DE-A-2442322	18-03-76	NONE	